



Berger Product Information

Digital Tent and Umbrella Navigator



item	product	width	weight	Coating	water tightness	water column	estimated life time of water tight coating	sol	UV	latex	dyesub direct	paper transfer	comments
		up to cm	g/m ²					Sol	UV	Latex	SUB water	SUB paper	
4413-77	rips FR+ws	310	240	one side PU	relatively watertight if processed with a slope	no	long	✓ ¹⁾	✓✓ ¹⁾	✓ ¹⁾	▪	✓	
4237-77	backlight satin FR+ws	310	175	one side PU	relatively watertight if processed with a slope	no	long	✓ ¹⁾	✓✓ ¹⁾	✓ ¹⁾	▪	✓	
4299-77	stretch canvas FR+ws	310	260	one side PU	relatively watertight if processed with a slope	no	long	✓ ¹⁾	✓✓ ¹⁾	✓ ¹⁾	✓ ²⁾	✓	
4418-77	universal tentex FR+ws	505	200	one side PU	relatively watertight if processed with a slope	no	long	✓ ¹⁾	✓ ¹⁾	✓ ¹⁾	▪	✓	
4499-77	universal lightex FR+ws	505	290	one side PU	relatively watertight if processed with a slope	no	long	✓ ¹⁾	✓ ¹⁾	✓ ¹⁾	▪	✓	
4280-77	universal display 250 FR+ws	505	250	one side PU	relatively watertight if processed with a slope	no	long	✓ ¹⁾	✓ ¹⁾	✓ ¹⁾	▪	✓	
4384-60	samba tent+s	150	120	one side PU	PU coated side is water-repellent	yes	long	✓ ¹⁾	✓ ¹⁾	✓ ¹⁾	▪	✓✓ ¹⁾	water column 700mm
4384-6266	samba FR+s	300	150	one side PU	PU coated side is water-repellent	yes	long	✓ ¹⁾	✓ ¹⁾	✓ ¹⁾	▪	✓	on stock March 2012
4289-6226	eco display 250 heavy Lotus+w **	310	250	one side PU	relatively watertight if processed with a slope	no	short ³⁾	▪	✓	✓ ¹⁾	✓	✓	can not stand heavy rain



printable with solvent & eco solvent inks



printable with UV inks



printable with Latex inks



direct printable with waterbased sublimation inks



sublimation with paper transfer

- ✓ ok
- ✓¹⁾ attention scatch resistance
- ✓✓¹⁾ recommended
- ✓²⁾ attention with too much ink, can lead to inkmigration
- ³⁾ grease, fat, oil will reduce the "lotus effect" over time
- not o.k.
- ** no topseller, production on demand



slope

www.bergertextil.com

Berger GmbH & Co. KG : Kuhleshütte 84 | 47809 Krefeld | Germany | phone: +49 (0)21 51 65231-0 | fax: +49 (0)21 51 65231-25

The information in this information sheet are based on findings obtained in practice. Because of the high number of factors which can have an effect during handling and application, customers tests will be required. A legally binding guarantee of specific properties is not to be inferred from our technical information. The information given here may subject to be changed without notice. This product does not require MSDS data sheets.